

3M**REACH**
1907/2007/EC

QS 200

Cold Shrink Single Core Inline Joint with Cold Shrink re-jacketing 93-AK 6x0-1 series

Application

The 3M™ QS 200 Cold Shrink Series Kits are designed for inline splicing up to 24kV Umax voltage class, Single core polymeric power cable systems with copper wire screen according to HD 620 (IEC 60502).

Splicing medium voltage power cables of different voltages classes and cross sections is possible.

Kit Content

The 93-AK 6x0-1 Inline Joint Series includes the Cold Shrink QS 200 silicone splice body with integrated stress control device, conductive electrode, silicone elastomeric insulation and outer semi-conductive layer. Also included are Copper Screen sleeve, Constant Force springs for metallic screen and thick walled EPDM rubber Cold Shrink outer tubes to re-build the cable outer jacket.



Product Features

- The versatile design of the prefabricated one-piece cold shrink splice body allows installation on a wide range of cable sizes and types and a fast and easy installation at temperatures ranging from - 20°C to + 50°C.
- No heat or flame is needed during splice body installation.
- Accommodates crimp or mechanical connectors up to 52mm diameter and 238mm length.
- Wide application range covering several cable cross sectional areas from 50mm² up to 630mm².
- Solderless earth connection by means of Copper Screen sleeve and Constant Force springs.
- Thick walled, EPDM rubber Cold Shrink outer re-jacketing tubes provide physical protection and moisture sealing of the completed Inline joints.
- No special tools needed during splice installation.

Installation

3M Cold Shrink technology ensures quick, easy and safe installation of the QS 200 Splice Body and outer protection tubes by pulling and unwinding the plastic support core in counter clockwise direction. Use of special tools is not necessary. Detailed instructions for installing the 3M QS 200 Series Inline Joints are included in each kit.

Product Selection

Application Range						
Kit Ref.	Cable Dimensions for Polymeric Cables				Connector Dimensions Crimp or Mechanical Connector	
	Diameter over Cable jacket max.(mm)	Diameter over Primary Insulation (mm)	Cross Section (mm ²)		Diameter max. (mm)	Length max. (mm)
			8,7/15(17,5)kV	12/20(24)kV 12,7/22(24)kV		
93-AK 620-1	46	19,1 – 38,0	95 - 400	50 - 300	38	160
93-AK 630-1	74	33,4 – 66,0	500 - 630	400 - 630	52	238*

*inclusive center rings

Performance Tests

The 3M QS 200 Inline Joint Series meets and exceeds the requirements of the European standard CENELEC HD 629.1 as well as IEC 60502-4. See Independent Test Report No. I-0600.

Testing

The QS 200 Kit Series 93-AK 620-1 up to 93-AK 630-1 were tested according HD 629.1 02/2006 S2 test sequence B1 Table 5

Type of Test according to HD 629.1 S2 B1 Table 5		Results
DC Voltage Withstand Test	6 x U _o ; t=15 min	passed
AC Voltage Withstand Test	4,5 x U _o ; t=5 min	passed
Partial Discharge Test	2 x U _o ; PD ≤ 10 pC	passed
Impulse Voltage Withstand Test	10 x 125kV positive and negative impulses	passed
Heat Cycle in air	63 cycles: 5h/3h	passed
Heat Cycle in water	63 cycles: 5h/3h	passed
Partial Discharge Test	2 x U _o ; PD ≤ 10 pC	passed
Impulse Voltage Withstand Test	10 x 125kV positive and negative impulses	passed
AC Voltage Withstand Test	2,5 x U _o ; t=15 min	passed

Product Identification

3M QS 200 Series Inline Joint kits are marked with supplier name, cable cross section ranges, voltage class and cable type, storage conditions and manufacturing codes for product traceability.

Storage:

The shelf life of 3M QS 200 Series Inline Joints is specified as 3 years.
Temperature: - 40°C to +50°C.

Product Stewardship:

3M has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis of our philosophy and policies by which we assess the health and environmental information on our products and then take the appropriate steps to protect employee, the public health and the environment.

Customer Notice:

3M encourages its customers and potential users of 3M products to review their applications for such products from the standpoint of human health and environmental quality. To help ensure that 3M products are not used in ways for which they were not intended or tested. 3M personnel are available to assist customers in dealing with ecological and product safety considerations. Your 3M sales representative can arrange for the proper contacts.

Regulatory Status:

3M QS 200 Series Inline Joints are not subject of the European WEEE and RoHS Directives but meet their requirements.

3M and Cold Shrink are trademarks of 3M Company

Important Notice

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized office of the Seller.

The statements contained herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY; INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY; FOR ANY INJURY OR FOR ANY DIRECT; INDIRECT; INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS.